

# MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN

## EC CERTIFICATE OF CONFORMITY 0432

### -CPD - 0082

In accordance with European Community Council Directive dated 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products (Construction Products Directive), amended by Council Directive 93/68/EEC of 22 July 1993, this certificate hereby confirms that the construction product

#### **NEMEF series 1739 and 1769 mortise locks**

Mortise locks for single-leaf doors in accordance with the drawing and classification in Appendix 2,

marketed by

**NEMEF BV**  
**Papegaaieweg 35**  
**7335 DK Wenum Wiesel**  
**Holland**

and manufactured in the production plants

#### **in accordance with Appendix 1**

is subjected by the manufacturer to an in-house production inspection as well as additional tests on samples taken at the factory in accordance with an established testing plan and that notified body no. 0432 – the MPA NRW – has conducted an initial test of the product's relevant properties, an initial inspection of the factory and the in-house production inspection and has conducted a running monitoring, assessment and approval of the in-house production inspection. This certificate confirms that all regulations on the certification of conformity and the performance properties described in Annex ZA to standard

#### **DIN EN 12209 :2004-03 + EN 12209 :2003/AC :2005**

were applied and that the product meets all requirements specified in it. This certificate was first issued on 06.04.2006 and is valid as long as the specifications in the aforementioned harmonised technical specification do not change significantly and provided that the manufacturing conditions in the plant or in the in-house production inspection system do not change significantly.

Dortmund, 21.04.2011



Dipl.-Ing. H. Jansen, Deputy  
Certification Office Director

THIS CERTIFICATE CONTAINS 1 PAGE AND 2 APPENDICES

Mortise locks in accordance with DIN EN for single-leaf wood/steel doors

**Production plants**

Production plant	Inspection mark
TESA S.A. C/Aramburuzabala, 23 E-20540 Esoriaza, Spain	DO 6.13
ASSA Abloy Romania S.R.L. 5 Preciiei Ave, sector 6 062202 Bucharest Romania	DO 6.15
Guli Security Product Limited 33-35 Chrysanthemum Road East Xialolan, Zhongshan, Guandong PR China, 528415 VR China	DO 6.14
Techno Precision Bujin Nanling Tsun Longshan ind. Zone Longgang 518123 Shenzen VR China	DO 6.16



Mortise locks in accordance with DIN EN for single-leaf wood/steel doors

Designation:

## NEMEF series 1769 mortise locks

### Lock

No.	Item No.	Type	Function	Backset	Distance	Face plate	Classification	Production plant
1	1769/xx	A	-	65 mm	72 mm PZ 74mm RZ	20 mm 24 mm	3   M   3   1 * )   0   F   6   H   C   2   0	DO 6.15
2	1769/yy	A	I	65 mm	72 mm PZ 74mm RZ	20 mm 24 mm	3   M   3   1 * )   0   F   6   H   C   2   0	DO 6.15
3	1769/zz	A	IIIa	65 mm	72 mm PZ 74mm RZ	20 mm 24 mm	3   M   3   1 * )   0   F   6   H   C   2   0	DO 6.15
4	1769/kk	A	-	65 mm	72 mm PZ 74mm RZ	20 mm 24 mm	3   M   3   1 * )   0   F   -   H   C   2   0	DO 6.15
5	1769/aa	A	-	65 mm	72 mm PZ 74mm RZ	20 mm 24 mm	3   M   5   1 * )   0   C   6   H   C   2   0	DO 6.14

Function: Standard version, no special function.

Function I: Single-piece follower, permanently active emergency exit door function.  
The door can be opened from the inside at all times using the fitting. It can be opened by key from the outside using the transmission.

Function IIIa: Split lock nut, permanently active emergency exit door function from the inside.  
The door can be opened from the inside at all times using the inside fitting. The outer fitting is engaged at all times. The bolt is only actuated from the outside by the key. After the fitting is actuated from the inside, the door can also be opened from the outside until it is manually relocked.

Type A For single-leaf doors  
Type B For the active leaf of two-leaf doors and single-leaf doors  
Type C For the inactive leaf of two-leaf doors.

### \*) Demonstrated fire resistance duration

Test report no. 3899/0243 MPA BS

Test report no. 2008-Efectis-R0218



## NEMEF series 1739 mortise locks

### Lock

No.	Item No.	Type	Function	Backset	Face plate	Classification	Production plant
1	1739/xx	A	-	65 mm	20 mm, 24 mm	1 3   M   3   1 * )   0   C   -   H   A   2   0	DO 6.13, DO 6.16
2	1739/xx	A	I-	65 mm	24 mm	1 3   M   3   I * )   0   C   -   H   A   2   0	DO 6.15
3	1739/yy	A	IIIa	65 mm	24 mm	1 3   M   3   1 * )   0   C   -   H   A   2   0	DO 6.15
4	1901/yy	A	IIIc	65 mm	24 mm	1 3   M   3   1 * )   0   C   -   H   A   2   0	DO 6.15

Function: Standard version, no special function.

Function I: Single-piece follower, permanently active emergency exit door function.  
The door can be opened from the inside at all times using the fitting. It can be opened by key from the outside using the transmission.

Function IIIa: Split lock nut, permanently active emergency exit door function from the inside.  
The door can be opened from the inside at all times using the inside fitting. The outer fitting is engaged at all times. The bolt is only actuated from the outside by the key. After the fitting is actuated from the inside, the door can also be opened from the outside until it is manually relocked.

Function IIIc: Split lock nut, permanently active emergency exit door function from the inside.  
The door can be opened from the inside at all times using the inside fitting. The outside fitting is engaged or disengaged using the key.

Type A For single-leaf doors  
Type B For the active leaf of two-leaf doors and single-leaf doors  
Type C For the inactive leaf of two-leaf doors

### \*) Demonstrated fire resistance duration

Test report no. 271 28149 ift

